

# 360L, ROTATING SPRAY HEAD TANK WASHING

Data Sheet 07021803 Rev.01

## SPRAY CHARACTERISTICS

Variable consumption of water and cycle times  
Total flow capacity governed by nozzle selection.  
360° Wash pattern.  
Working Pressure of 5 - 10 bar.

## NOZZLE PROPERTIES

Self cleaning and lubricating design  
Various connections available, Male or Female  
Cleans vessel and tanks up to 20 meters in diameter  
Suitable for Dairy, Food, Chemical  
Bespoke designs available  
No process contamination  
High efficiency design

**KAITE**

tel: **+44 (0) 1744 607361**

email: **sales@kaite.eu**

web: **kaite.eu**



## Capacity Chart, 360L Rotating Spray Head

PRESSURE Bar.G	4 x 5mm		2 x 6mm		2 x 7mm		4 x 8mm		2 x 10mm		2 x 12.5mm	
	Flow m <sup>3</sup> /hr	Jet Length m	Flow m <sup>3</sup> /hr	Jet Length m	Flow m <sup>3</sup> /hr	Jet Length m	Flow m <sup>3</sup> /hr	Jet Length m	Flow m <sup>3</sup> /hr	Jet Length m	Flow m <sup>3</sup> /hr	Jet Length m
5	9.4	4.9	6.3	6.5	8.1	7.8	20.0	9.0	17.4	13.0	26.4	13.0
6	10.4	5.5	7.1	7.1	9.2	8.5	22.0	9.9	19.2	14.5	28.8	15.0
7	11.1	6.4	7.8	8.0	10.0	9.5	23.6	10.6	21.0	16.0	31.2	17.0
8	11.7	7.3	8.3	9.2	10.8	10.4	25.0	11.2	22.0	17.5	33.0	18.5
9	12.1	8.5	8.8	10.2	11.5	11.5	26.4	12.2	23.4	19.0	34.8	20.0
10	9.0	9.0	9.2	11.5	12.0	12.0	27.5	13.0	24.2	20.0	35.5	21.0